



KHOSRO NIKOO PLAST
INDUSTRIAL GROUP

NIKOO POLYMER

Zinc Stearate





KHOSRO NIKOO PLAST
INDUSTRIAL GROUP

NIKOO POLYMER



Zinc Stearate

Product description

For enhancing the heat stability and improve the melt flow of PVC in production of UPVC pipes, fittings, wall coatings and window profiles the zinc stearate is used. This product is formed by reaction of zinc oxide and stearic acid and it is a completely safe material.

KEY FEATURES AND BENEFITS

- Economical
- Availability
- No dust (it is made in flake form)
- Suitable for a variety of UPVC products

TYPICAL PROPERTIES

Property	Zinc Stearate 1005
Appearance	White flakes
Moisture, % by weight	0.1
Free fatty acids, % by weight	0.5
Ash Content, % by weight	22
Melting Point, (°C)	125
Form	Flake





KHOSRO NIKOO PLAST
INDUSTRIAL GROUP

NIKOO POLYMER



Zinc Stearate

APPLICATION

- Heat stabilizer
- External lubrication
- Color improver

The application dosage of this product depends on the consumer's demand. But in common it is recommended to use at least 1.5 to 2 phr.

PACKAGING AND STORAGE

- The product is packed in 25 Kg pockets.
- It is better to store this product in a cool and dry place and specially far from the hot sources.



گروه صنعتی خسرو نیکو پلاست

نیکو پلیمر

- انواع استابلایزر های PVC
- کامپاند های PVC
- استئارات پایه فلزی (Ca, Zn, Mg)
- کمک فرآیند ها و روان کننده های پلیمری

WWW.KNP-CO.COM

TEL: +98 41 4143

Khosro Nikoo Plast Industrial Group
3 Kilometers after Tabriz-Azarshahr Police Station , Tabriz , Iran